



TOC cuvette test (difference method) 60-735 mg/L C, 25 tests

Product #:

LCK381

AED Price:

Contact Hach

Hazardous



LCK cuvette tests: Minimum amounts of reagents, maximum safety.

Pre-dosed reagents for maximum safety. Easy to use and photometric evaluation, packaged in a fully equipped box. Environmentally friendly due to less chemicals.

Precise and reliable measurement values

Maximum safety for users, thanks to the closed system and low amounts of reagents

Convenient and error-free dosing of the reagents

Barcode label for automatic recognition in the photometer

Differentiation between tests and measuring ranges by means of colour-coding

Specifications

According to standard:	DIN 38409-H3
Description:	Total Organic Carbon
Digestion required:	Yes
EPA compliant:	N/A
Instrument:	DR3900, DR6000, DR1900, DR2800, DR3800, DR5000
Measuring range:	60 - 735 mg/L C
Measuring range (2):	TC 75 - 750 mg/L C
Measuring range (3):	TIC 15 - 150 mg/L C
Method:	Difference Method (TOC is determined as the difference between the TC and TIC values), Persulphate Digestion
Number of tests:	25
Parameter:	TOC
Platform:	LCK
Storage conditions:	15 - 25 °C

Required Accessories

- Gloves, Disposable, Powder Free, Nitrile, Large (Item 2550503)