



Nitrite cuvette test 0.6-6.0 mg/L NO₂-N, 25 tests

Product #:

LCK342

Hazardous

AED Price:

Contact Hach



LCK cuvette tests: Minimum amounts of reagents, maximum safety.

Pre-dosed reagents for maximum safety. Easy to use and photometric evaluation, packaged in a fully equipped box. Officially approved for consent limits. Environmentally friendly due to less chemicals.

Precise and reliable measurement values

Maximum safety for users, thanks to the closed system and low amounts of reagents

Convenient and error-free dosing of the reagents

Barcode label for automatic recognition in the photometer and Truecal calibration

Differentiation between tests and measuring ranges by means of colour-coding

Specifications

According to standard:	EN ISO 26777, DIN 38405 D10
EPA compliant:	N/A
Instrument:	DR3900, DR6000, DR1900, DR2800, DR3800, DR5000
Measuring range:	0.6 - 6.0 mg/L NO ₂ -N
Measuring range (2):	2 - 20 mg/L NO ₂
Method:	Diazotisation
Number of tests:	25
Parameter:	Nitrite
Platform:	LCK
Standard method:	EN ISO 26777
Storage conditions:	15 - 25 °C
Truecal:	Yes

Required Accessories

- Gloves, Disposable, Powder Free, Nitrile, Large (Item 2550503)