



## Buret, Automatic, Self-Zeroing, 25 mL Buret Capacity

<b>Product #:</b>	<b>2087640</b>
AED Price:	Contact Hach
Available	

Durable, crystal-clear acrylic buret is calibrated to meet ASTM E287 requirements. Leak-proof stopcock with self-lubricating PTFE TFE plug. Unaffected by dilute mineral acids and bases (except hydrofluoric acid and ammonium hydroxide). Handles liquids with a pH range of 1 - 14 and up to 5% wt/wt of acids or 30% bases can be used. Not designed for exposure to alcohol or organic solvents. Includes low density polyethylene squeeze bottle and 36" tubing for easy self-zeroing set up for titration work stations. Dust cover included.

### Calibrated

Individually calibrated to meet accuracy of ASTM\* E287 for repeatable, accurate results

### Chemical compatibility

Can be used with dilute mineral acids and bases except hydrofluoric acid and ammonium hydroxide

### Wide pH range

pH range of 1 - 14 is ideal; compatible with up to 5% wt/wt acids and up to 30% bases accommodating a wide range of tirants

### All-inclusive buret kit

Comes complete with everything you need to get started: acrylic buret, LDPE squeeze bottle assembly, 3 ft. (91 cm) PVC tubing, and buret cover

### Easy to read

Transparent/Graduated

---

## Specifications

Capacity:	25 mL
Housing material:	Glass
Special Features:	Buret, Automatic, Self-Zeroing