



pH Encapsulated Sensor, LCP Body, 5 Wire, Union Mount, High Purity Water Glass, Low Conductivity, 3 m Cable

Product #:

6058P4

AED Price:

Contact Hach

Ships within 2 weeks

LCP (Liquid Crystal Polymer), Union Mounting Style, 3 m Analogue Cable, 5-Wire with Built-In Preamplifier, pH Glass Electrode for Low Conductivity Solutions

Exceptional Performance with the Differential Electrode Measurement Technique

This field-proven technique uses three electrodes instead of the two normally used in conventional pH sensors. Process and reference electrodes measure the pH differentially with respect to a third ground electrode. The end result is unsurpassed measurement accuracy, reduced reference junction potential, and elimination of sensor ground loops. These sensors provide greater reliability, resulting in less downtime and maintenance.

Lower Maintenance Needs with the Replaceable Salt Bridge

The salt bridge creates a barrier to contamination which minimizes the dilution of the internal standard cell solution. The result is lower maintenance needs and a longer time period between calibrations.

Built-in Preamp or Two-Wire Transmitter

The built-in preamp produces a strong signal, enabling you to locate the analyser up to 914 m (3000 ft.) from the sensor. An optional built-in two-wire transmitter is available for applications requiring a 4-20 mA sensor signal. This option requires that the indicating instrument of the measuring system be capable of providing 24 VDC to power the sensor, and have adjustment means to calibrate for zero offset and span.

Versatile Mounting Styles

1.5 inch NPT threads are provided on both ends of the convertible mounting style sensor for either mounting into a pipe tee or attaching to the end of a pipe for immersion. The convertible style enables you to consolidate inventory, and thereby reduce associated costs. A union-mount style sensor and mounting tee are also available to conveniently install and remove the sensor for in-line service.

Specifications

Cable length:	10 '
Housing material:	LCP
Junction:	PVDF Junction
Material (electrode):	Glass
Mounting:	Union
Warranty:	24 months
What's included?:	Includes: sensor with 10 ft cable, union mount and manual

What's included?

Includes: sensor with 10 ft cable, union mount and manual