



## 3725 sc Digital inductive conductivity sensor, PP, convertible

**Product #:** D3725E2T.99  
**AED Price:** Contact Hach

Immersion or flow-through sensor consisting of analogue sensor with 6m cable and digital gateway with 1m connection cable for SC controller

**For highly contaminated fluids**

**Factory calibrated**

**Available in different materials and mounting kits**

---

### Specifications

Body Material:	Polypropylene
Cable length:	6 m
Flow:	max. 3 m/s
Immersion depth:	79.2 mm
Length:	127 mm
Material:	Polypropylene (PP)
Measuring range:	200 $\mu$ S/cm - 2000 mS/cm
Mounting:	Convertible
Operating temperature range:	-10 - 100 °C (Sensor - limited by body material)
Pressure range:	6.9 bar at 100°C
Sensor type :	Digital
Special notes:	Composed of 3725E2T analogue sensor with 6 m fixed cable, AD gateway and 1m digital cable.
Temperature sensor:	Pt1000 RTD
Warranty:	24 months
Wetted Materials:	Polypropylene
What's included?:	Includes: sensor with cable, digital gateway, extension cable and manual

---

### What's included?

Includes: sensor with cable, digital gateway, extension cable and manual

---

## Required Accessories

- SC1000 Probe Module, 4 Sensor Connectors, 4 mA Output, 4 Relays, 100-240 VAC, with EU plug (Item LXV400.99.2R121)
- SC1000 Display Module (Item LXV402.99.00001)
- SC4500 Controller, Prognosys, 5x mA Output, 2 digital Sensors, 100-240 VAC, without power cord (Item LXV525.99A11551)
- SC4500 Controller, Prognosys, 5x mA Output, 1 digital Sensor, 100-240 VAC, without power cord (Item LXV525.99A11501)
- SC4500 Controller, Prognosys, 5x mA Output, 2 digital Sensors, 24 VDC, without plug (Item LXV525.99Z11551)