



BOD Trak II Manometric BOD apparatus with accessories

Product #:

2952400

Hazardous

AED Price:

Contact Hach

Ships within 3 days



Manometric BOD(n) laboratory measurement station, control unit and stirrer with pressure sensors for 6 bottles.

BOD measurement programmes for 5, 7, 10 days, OECD biodegradation test for 30 days.

Measuring range 0-700 mg/L O₂, variable.

Incl. 6 rubber sleeve stoppers, 6 492-mL brown glass bottles, grease, 6 magnetic stirrers, funnel, 1 pkg LiOH Powder Pillows, 1 pkg nutrient Powder Pillows.

Specifications

BOD Bottle:	473 mL/6 pcs
Capacity:	Six 492 mL bottles
Drift:	< 3 mg/L BOD in 5 days
Input (voltage):	110 - 240 V, 50/60 Hz
Instrument:	BOD Trak II Apparatus
Interface:	RS232
Measurement method:	Manometric
Measuring range:	0 - 700 mg/L
Output Voltage:	24V, UL CSA, and TUV approved
Warranty:	24 months
Weight:	4 kg
What's included?:	BOD Trak II instrument, Power cord, 230 VA harmonized power cord with continental European plug; Seal cups (6x); BODTrack II amber sample bottles (6x); BOD Trak II Magnetic stir bars (6x); Spatula scoop; Nutrient Buffer solution pillows (1 pk); potassium hydroxide pellets (1 container)

What's included?

BOD Trak II instrument, Power cord, 230 VA harmonized power cord with continental European plug; Seal cups (6x); BODTrack II amber sample bottles (6x); BOD Trak II Magnetic stir bars (6x); Spatula scoop; Nutrient Buffer solution pillows (1 pk); potassium hydroxide pellets (1 container)