



## Sension+ 5060 portable platinum conductivity cell for general purpose applications

**Product #:** LZW5060.97.0002  
**AED Price:** Contact Hach  
**Available**

Conductivity cell with Pt electrodes and Polycarbonate body.

Cell constant  $k=1\text{ cm}^{-1}$ . Automatic temperature compensation. 1m cable. For portable meters.

Measuring range  $0.2\text{ }\mu\text{S/cm}$  -  $200\text{ mS/cm}$ ,  $0 - 80\text{ }^{\circ}\text{C}$ .

The electrode is suitable for general aqueous applications.

**Ergonomic and robust**

---

### Specifications

Accuracy:	0.50% with EC5 Meter
Cable length:	1 m
Connector:	Sension+ MP5
Dimensions (D x L):	12 mm x 85 mm
Electrode type:	Portable
Length:	85 mm
Material:	Sensor Body: Outside: Polycarbonate; Inside: Glass
Measuring range conductivity:	$0.2\text{ }\mu\text{S/cm}$ - $200\text{ mS/cm}$
Parameter:	Conductivity
Sensor type :	3-pole Platinum, $k = 1.0\text{ cm}^{-1}$
Temperature range:	$0 - 80\text{ }^{\circ}\text{C}$
Thermistor:	Pt 1000
Type:	Portable
Warranty:	12 months