



Sensation+ ISE combination electrode, fluoride, fixed cable 1 m, BNC

Product #: LZW9655C.97.002

AED Price: Contact Hach
Available

Ion-selective combination electrode for Fluoride measurements. Range 0.02-20,000 mg/L F⁻, 5-50 °C. With 1 m cable and BNC connector.

Requires virtually no maintenance

The solid-state sensor design allows for DRY storage of the ISE without a shelf life or membrane replacement.

Provides fast, stable, and accurate response in a variety of sample types

Specifications

| | |
|----------------------|---|
| Accuracy: | ±0.02 mV or 0.05%, whichever is greater (application dependent) |
| Cable length: | 1 m |
| Connector: | BNC Connector |
| Dimensions (D x L): | 12 mm x 120 mm |
| Electrode junction : | Porous PTFE Annular Ring |
| Electrode type: | Laboratory Combination ISE |
| Filling solution: | Non-refillable Dritek gel |
| ISA required: | 258999 |
| Length: | 120 mm |
| Material: | Sensor Body: Epoxy |
| Measuring range: | 0.01 - 19000 mg/L F ⁻ |
| Parameter: | Fluoride |
| Sensor type : | Solid-state crystal membrane |
| Special Features: | Combination electrode. Maintenance free: No electrolyte or spare membranes needed |
| Temperature range: | 5 - 50 °C |
| Type: | Lab ISE combination |
| Warranty: | 6 months |