



TOC cuvette test (difference method) 2-65 mg/L C, 25 tests

Product #:

LCK380

AED Price:

Contact Hach

Hazardous



LCK cuvette tests: Minimum amounts of reagents, maximum safety.

Pre-dosed reagents for maximum safety. Easy to use and photometric evaluation, packaged in a fully equipped box. Approved for consent limits. Environmentally friendly due to less chemicals.

Precise and reliable measurement values

Maximum safety for users, thanks to the closed system and low amounts of reagents

Convenient and error-free dosing of the reagents

Barcode label for automatic recognition in the photometer

Differentiation between tests and measuring ranges by means of colour-coding

Specifications

According to standard:	DIN 38409-H3
Description:	Total Organic Carbon
Digestion required:	yes
EPA compliant:	N/A
Instrument:	DR3900, DR6000, DR1900, DR2800, DR3800, DR5000
Measuring range:	2 - 65 mg/L C
Measuring range (2):	TC 12 - 75 mg/L C
Measuring range (3):	TIC 10 - 73 mg/L C
Method:	Difference Method (TOC is determined as the difference between the TC and TIC values), Persulphate Digestion
Number of tests:	25
Parameter:	TOC
Platform:	LCK
Storage conditions:	15 - 25 °C

Required Accessories

- Gloves, Disposable, Powder Free, Nitrile, Large (Item 2550503)