



## TOC cuvette test (difference method) 60-735 mg/L C, 25 tests

Product #:

LCK381

AED Price:

Contact Hach

Hazardous



### LCK cuvette tests: Minimum amounts of reagents, maximum safety.

Pre-dosed reagents for maximum safety. Easy to use and photometric evaluation, packaged in a fully equipped box. Environmentally friendly due to less chemicals.

**Precise and reliable measurement values**

**Maximum safety for users, thanks to the closed system and low amounts of reagents**

**Convenient and error-free dosing of the reagents**

**Barcode label for automatic recognition in the photometer**

**Differentiation between tests and measuring ranges by means of colour-coding**

---

### Specifications

According to standard:	DIN 38409-H3
Description:	Total Organic Carbon
Digestion required:	Yes
EPA compliant:	N/A
Instrument:	DR3900, DR6000, DR1900, DR2800, DR3800, DR5000
Measuring range:	60 - 735 mg/L C
Measuring range (2):	TC 75 - 750 mg/L C
Measuring range (3):	TIC 15 - 150 mg/L C
Method:	Difference Method (TOC is determined as the difference between the TC and TIC values), Persulphate Digestion
Number of tests:	25
Parameter:	TOC
Platform:	LCK
Storage conditions:	15 - 25 °C

---

### Required Accessories

- Gloves, Disposable, Powder Free, Nitrile, Large (Item 2550503)