



DRB200 Dry thermostat with 1 heating block, 9 x 13 mm / 2 x 20 mm

Product #: LTV082.99.10001

AED Price: Contact Hach

Thermostat DRB 200 – the simple solution for all digestions

Equipped with a large readable display and a digital timer with an automatic switch-off and acoustic signal. Operational safety guaranteed by protection lid covering the heating block, by the insulated external shell and by an integrated anti-overheating feature. Cuvettes and reaction vessels can be digested at large scale of different temperatures and time settings. Temperature stability and reproducibility ensured.

Great flexibility

Pre-programmed for all

standard digestions and freely programmable for user-specific digestions

Excellent reproducibility

Temperature stability

Simple handling

Large, easily readable display and one-key operation for standard

digestions

Specifications

Display resolution:	5 x 7 dot matrix
Display size:	2 x 16 character
Heating programmes:	Pre-programmed for 40°C,100°C,150°C,165°C and freely selectable 37-165°C, 1-480 min
Heating rate:	From 20 °C - 150 °C in 10 minutes
Heating system:	1 Heating Block
Manual languages:	English, French, German, Italian, Spanish, Dutch, Swedish, Danish, Polish
Max. operating humidity:	90 %
Number of cuvettes:	9 x 13 mm diameter
Number of cuvettes (2):	2 x 20 mm diameter
Operating temperature range:	10 - 45 °C
Power requirements (Voltage):	115/220 V AC
Power supply:	115 V - 230 V +5%/-15%
Safety checks:	CE, GS, cTUVus
Storage conditions:	-40 °C - 60 °C

Temperature stability:	1 °C
User interface:	3 softkeys
User programmes:	6 free temperature/time
Warranty:	24 months
Weight:	2 kg