



LT200 Dry thermostat with 2 blocks, 15 x 13 mm, 15 x 13 mm

Product #: LTV082.99.23002

AED Price: Contact Hach

Thermostat LT200 for standard and special digestions

Pre-programmed for all standard digestions and freely programmable for user specific digestions

2 separately controllable heating blocks with separate protection covers, both blocks each with 15x13mm holes

Illuminated digital display for remaining time/temperature and operator guidance

3 pre-programmed and 6 freely programmable storage spaces

Temperature settings between 37°C and 150°C in 1°C steps, time setting between 1 and 480 min

Great flexibility

Excellent reproducibility

Simple to use

Specifications

Dimensions (H x W x D):	145 mm x 250 mm x 310 mm
Display resolution:	5 x 7 dot matrix
Display size:	2 x 16 Character
Display type:	LCD
Heating programmes:	Preprogrammed for 40°C, 100°C, 148°C and freely selectable 37-150°C, 1-480 min.
Heating rate:	from 20 to 148 °C in 10 minutes
Manual languages:	English, French, German, Italian, Spanish, Dutch, Swedish, Polish
Max. operating humidity:	90 %
Number of cuvettes:	15 x 13 mm diameter
Number of cuvettes (2):	15 x 13 mm diameter
Operating temperature range:	10 - 45 °C
Power requirements (Voltage):	115/220 V AC
Power supply:	115 V - 230 V +5%/-15%,
Safety checks:	CE, GS, cTUVus
Storage conditions:	-40 - 60 °C

Temperature stability:	± 1 °C in conformity with EN, ISO, EPA methods
User interface:	3 softkeys
User programmes:	6 free temperature/time
Warranty:	24 months
Weight:	2.8 kg