



34" Combination ORP Sensor, Convertible Style, PPS Body, Platinum Electrode Type- HF-Resistant Glass with PEI, 4.5 m Cable

Product #: RC1R5N-HF

AED Price: Contact Hach

Call for ship date

PPS, convertible body style, 4.5 m analog cable, platinum electrode, no temperature compensation, HF-resistant glass

Low Price - Great Performance

These combination sensors are designed for specialty applications for immersion or in-line mounting. The reference cell features a double-junction design for extended service life, and a built-in solution ground. The body is molded from chemically-resistant PPS or PVDF, and the reference junction is coaxial porous PTFE. All sensors are rated 0 to 105 °C up to 100 psig, and have integral 4.5 m (15 ft.) cables with tinned leads. The PC-series (for pH) and RC-series (for ORP) combination sensors are ideal for measuring mild and aggressive media.

Special Electrode Configurations

Sensors with rugged dome electrodes, "easy-to-clean" flat glass electrodes, and even HF (hydrofluoric acid) resistant glass electrodes are available for a wide variety of process solutions.

Temperature Compensation Element Option

The PC-series combination pH sensors are available with or without a Pt 1000 ohm RTD temperature element. The RC-series combination ORP sensors are supplied without a temperature element.

Versatile Mounting Styles

Sensors are available in three mounting styles - convertible, insertion, and sanitary.

Full-Featured "Plug and Play" Hach Digital SC Controllers

There are no complicated wiring or set up procedures with any Hach SC controller. Just plug in any combination of Hach digital sensors and it's ready to use-it's "plug and play." One or multiple sensors-the SC controller family allows you to receive data from up to eight Hach digital sensors in any combination using a single controller.

Specifications

Electrode type: Convertible

Housing material: PPS, HF Glass

Material: Platinum

Parameter: ORP

Warranty: 3 months

What's included?: Includes: sensor with 15 ft cable and manual

None

What's included?

Temperature compensation:

