



Sension+ 5064 Robust conductivity cell for field use, attractive priced

Product #: LZW5064.97.0002
AED Price: Contact Hach

Robust conductivity cell with Titanium electrodes and Polycarbonat body for Sension+ portable meters. Cell constant $k=1\text{ cm}^{-1}$. Built-in Pt1000 for automatic temperature compensation. 1 m cable, MP5 connector.

Measuring range 5 $\mu\text{S/cm}$ - 50 mS/cm , 0 - 80 °C. Robust conductivity cell for general aqueous application with attractive price position.

Attractive price

Built-in Pt1000 for automatic temperature compensation.

Specifications

Accuracy:	0.50% with EC5 Meter
Cable length:	1 m
Connector:	Sension+ MP5
Dimensions (D x L):	12 mm x 85 mm
Electrode type:	Portable
Length:	85 mm
Material:	Sensor Body Outside: Polycarbonate; Inside: Glass, Sensor Cell: Titanium
Measuring range conductivity:	5 $\mu\text{S/cm}$ - 50 mS/cm
Parameter:	Conductivity
Sensor type :	2-pole Titanium, $k = 1\text{ cm}^{-1}$
Temperature range:	0 - 80 °C
Thermistor:	Pt1000
Warranty:	6 months