



# EZ4005 Ammonium Analyser

Product #: EZ4005.XXXXXXXX

AED Price: Contact Hach

## Online automatic titration of Ammonium in water

EZ4000 Series Analysers are single-parameter titrators that achieve excellent precision and accuracy. Depending on the parameter of interest, the measuring range and the water matrix the EZ4000 Series may use either potentiometry i.e. acid-base, redox or precipitation titration, where the endpoint is determined by a change in a specific variable, or photocolorimetry, where colour change is used to determine the endpoint of the titration. The high precision dispenser for addition, robust peristaltic pumps for sampling and drain, and carefully designed liquid pathways all add up to the highest performance for industrial and environmental analysis needs.

#### Results you can rely on

Smart automatic features for validation, priming and cleaning are embedded in the controller software and contribute to analytical performance, maximised uptime and negligible operator invervention. Sample lines and analysis vessel are cleaned with demineralised water to eliminate cross contamination between samples. Electronic and wet-chemical part of the analyser are strictly separated. A transparent door allows for instant visual inspection of the wet part.

### Flexibility that meets your needs

EZ Series Ammonium Analysers come in an attractive, ergonomic mainframe with a compact footprint. All hardware is controlled by the integrated industrial panel PC. The modular build allows for the analyser to match your application and operational needs.

- The standard measuring range can be narrowed by a different calibration range or extended via internal dilution options.
- Analogue and digital output options
- Multiple stream analysis for up to 8 sample streams

There are many additional options available. Please contact Hach for more details.

## **Specifications**

Alarm: 1 x malfunctioning, 4 x user-configurable, max. 24 VDC/0.5 A, potential free contacts

Ambient temperature: 10 - 30 °C ±4 °C deviation at 5 - 95% relative humidity (non-condensing)

Analogue outputs: Active 4 - 20 mA max. 500 Ohm load, standard 1, max. 8 (option)

Calibration: N.A.

Certifications: CE compliant / UL certified

Cycle Time: 10 - 15 minutes

Demineralised water: For rinsing / dilution

Detection limit:  $\leq 10 \text{ mg/L}$ 

Digital outputs: Optional: Modbus (TCP/IP, RS485)

Dimensions (H x W x D): 690 mm x 465 mm x 330 mm

Drain: Atmospheric pressure, vented, min. Ø 32 mm

Earth connection: Dry and clean earth pole with low impedance (< 1 Ohm) using an earth cable of > 2.5 mm<sup>2</sup>

Flow rate: 100 - 300 mL/min

Instrument air: Dry and oil free according to ISA-S7.0.01-1996 quality standard for instrument air

Interferences: Soaps, oily matter, suspended solids or precipitates may coat the glass electrode and cause a

sluggish response. Allow additional time between titrant additions to let the electrode come to equilibrium or clean the electrodes occasionally. Alkaline compounds may interfere with the

titration.

Material: Hinged part: Thermoform ABS, door: PMMA

Wall section: Galvanised steel, powder coated

Measurement method: Acid-base titration with sulphuric acid, conform with standard method APHA 4500-NH3

Measuring range:  $100 - 5000 \text{ mg/L NH}_4$ 

Optional:

10 - 500 mg/L NH<sub>4</sub>

25 - 1250 mg/L NH<sub>4</sub>

 $50 - 2500 \text{ mg/L NH}_4$ 

Model: EZ4005

Number of sample streams: 1, 2, 4 or 8
Parameter: Ammonium

Power: 100 - 240 VAC, 50/60 Hz

Max. power consumption: 120 VA

Power supply: 100 - 240 VAC, 50/60 Hz

Precision: Better than 2% full scale range for standard test solutions

Protection class: Protection class: Analyser cabinet: IP44 / Panel PC: IP65

Reagent Requirements: Keep between 10 - 30 °C
Sample pressure: By external overflow vessel

Sample quality: Maximum particle size 100 μm, < 0.1 g/L; Turbidity < 50 NTU

Sample temperature: 10 - 30 °C

Validation: Automatic; frequency freely programmable

Warranty: 24 months
Weight: 25 kg

What's included?: EZ4005 Ammonium Analyser, Instruction Manual, 1 x Double Bit Door Key, 1 x Mounting

Brackets, 1 x pH Electrode, Routine S7 Connection,

1 x empty 5L Reagent Container with Fittings (for H, SO, Solution) and 1 x empty 10L Reagent

Container with Fittings (for NaOH Solution)

EZ4005 Ammonium Analyser, Instruction Manual, 1 x Double Bit Door Key, 1 x Mounting Brackets, 1 x pH Electrode, Routine S7 Connection, 1 x empty 5L Reagent Container with Fittings (for  $H_2SO_4$  Solution) and 1 x empty 10L Reagent Container with Fittings (for NaOH Solution)