



Be Right™



EZ1022 Hydrogen Peroxide Analyser

Product #: EZ1022.XXXXXXXXXX
AED Price: Contact Hach

Online colorimetric analysis of Hydrogen Peroxide (H₂O₂) in water

EZ1000 Hydrogen Peroxide Analysers achieve excellent precision and accuracy. At the heart of the colorimeter there is a compact photometer assembly developed especially for the EZ Series. Consumption of reagents is reduced by low volume analysis, yet high sensitivity is assured by a long optical path length. The limit of detection is in the low µg/L range.

Results you can rely on

Smart automatic features for calibration, validation, priming and cleaning are embedded in the controller software and contribute to analytical performance, maximised uptime and negligible operator intervention. Precision micropumps dose all reagents. Sample lines and analysis vessel are cleaned with demineralised water to eliminate cross contamination between samples. Electronic and wet-chemical part of the analyser are strictly separated. A transparent door allows for instant visual inspection of the wet part.

Flexibility that meets your needs

EZ Series Hydrogen Peroxide Analysers come in an attractive, ergonomic mainframe with a compact footprint. All hardware is controlled by the integrated industrial panel PC. The modular build allows for the analyser to match your application and operational needs.

- The standard measuring range can be narrowed by a different calibration range or extended via internal dilution options.
- Analogue and digital output options
- Multiple stream analysis for up to 8 sample streams

There are many additional options available. Please contact Hach for more details.

Specifications

| | |
|----------------------|---|
| Alarm: | 1 x malfunctioning, 4 x user-configurable, max. 24 VDC/0.5 A, potential free contacts |
| Ambient temperature: | 10 - 30 °C ± 4 °C deviation at 5 - 95% relative humidity (non-condensing) |
| Analogue outputs: | Active 4 - 20 mA max. 500 Ohm load, standard 1, max. 8 (option) |
| Automatic cleaning: | Yes |
| Calibration: | Automatic, 2-point; frequency freely programmable |
| Certifications: | CE compliant / ETL certified |
| Cycle Time: | 10 min (dilution + 5 min.) |

| | |
|---------------------------|--|
| Demineralised water: | For rinsing / dilution |
| Detection limit: | ≤ 2 µg/L |
| Digital outputs: | Optional: Modbus (TCP/IP, RS485) |
| Dimensions (H x W x D): | 690 mm x 465 mm x 330 mm |
| Drain: | Atmospheric pressure, vented, min. Ø 32 mm |
| Earth connection: | Dry and clean earth pole with low impedance (< 1 Ohm) using an earth cable of > 2.5 mm ² |
| Flow rate: | 100 - 300 mL/min |
| Instrument air: | Dry and oil free according to ISA-S7.0.01-1996 quality standard for instrument air |
| Interferences: | Oxidants like Bromine, Bromamine, Chlorine, Copper Cu(II) > 8 mg/L, Chromate, Iodine, Iodoamines, Iron Fe(III) > 20 mg/L, Nitrite, Ozone and Manganese may oxidize the DPD colour solution. Large amounts of colour and turbidity interfere. Fats, oil, proteins, surfactants and tar. |
| Material: | Hinged part: Thermoform ABS, door: PMMA Wall section: galvanised steel, powder coated |
| Measurement method: | Colorimetric measurement at 510 nm using DPD |
| Measuring range: | 5 - 500 µg/L H ₂ O ₂ Optional: 2 - 125 µg/L 2 - 250 µg/L 0.04 - 2.0 mg/L (with internal dilution) 0.08 - 4.0 mg/L (with internal dilution) 0.5 - 50 mg/L (with internal dilution) |
| Model: | EZ1022 |
| Number of sample streams: | 1, 2, 4, or 8 |
| Parameter: | Hydrogen Peroxide |
| Power: | 100 - 240 VAC, 50/60 Hz Max. power consumption: 120 VA |
| Power supply: | 100 - 240 VAC, 50/60 Hz |
| Precision: | Better than 2% full scale range for standard test solutions |
| Protection class: | Protection class: Analyser cabinet: IP44 / Panel PC: IP65 |
| Reagent Requirements: | Keep refrigerated. |
| Sample pressure: | By external overflow vessel |
| Sample quality: | Maximum particle size 100 µm, < 0.1 g/L; Turbidity < 50 NTU |
| Sample temperature: | 10 - 30 °C |
| Validation: | Automatic; frequency freely programmable |
| Warranty: | 24 months |
| Weight: | 25 kg |
| What's included?: | EZ1022 Hydrogen Peroxide Analyser, Instruction Manual, 1 x Double Bit Door Key, 1 x Mounting Brackets and 2 x empty 2.5L Glass Containers with Fittings (for Colour and Buffer Solution) |

What's included?

EZ1022 Hydrogn Peroxide Analyser, Instruction Manual, 1 x Double Bit Door Key, 1 x Mounting Brackets and 2 x empty 2.5L Glass Containers with Fittings (for Colour and Buffer Solution)