



# EZ1027 Nickel Ni(II) Analyser

Product #: EZ1027.XXXXXXXX

AED Price: Contact Hach

## Online colorimetric analysis of dissolved Nickel in water

EZ1000 Nickel Analysers achieve excellent precision and accuracy. At the heart of the colorimeter there is a compact photometer assembly developed especially for the EZ Series. Consumption of reagents is reduced by low volume analysis, yet high sensitivity is assured by a long optical path length. The limit of detection is in the low µg/L range.

#### Results you can rely on

Smart automatic features for calibration, validation, priming and cleaning are embedded in the controller software and contribute to analytical performance, maximised uptime and negligible operator intervention. Precision micropumps dose all reagents. Sample lines and analysis vessel are cleaned with demineralised water to eliminate cross contamination between samples. Electronic and wet-chemical part of the analyser are strictly separated. A transparent door allows for instant visual inspection of the wet part.

#### Flexibility that meets your needs

EZ Series Nickel Analysers come in an attractive, ergonomic mainframe with a compact footprint. All hardware is controlled by the integrated industrial panel PC. The modular build allows for the analyser to match your application and operational needs.

- The standard measuring range can be narrowed by a different calibration range or extended via internal dilution options.
- Analogue and digital output options
- Multiple stream analysis for up to 8 sample streams

There are many additional options available. Please contact Hach for more details.

### **Specifications**

Alarm: 1 x malfunctioning, 4 x user-configurable, max. 24 VDC/0.5 A, potential free contacts

Ambient temperature:  $10 - 30 \text{ °C} \pm 4 \text{ °C}$  deviation at 5 - 95% relative humidity (non-condensing)

Analogue outputs: Active 4 - 20 mA max. 500 Ohm load, standard 1, max. 8 (option)

Automatic cleaning: Yes

Calibration: Automatic, 2-point; frequency freely programmable

Certifications: CE compliant / UL certified

Cycle Time: 10 minutes (dilution + 5 min.)

Demineralised water: For rinsing / dilution

Detection limit:  $\leq 5 \mu g/L$ 

Digital outputs: Optional: Modbus (TCP/IP, RS485)

Dimensions (H x W x D): 690 mm x 465 mm x 330 mm

Drain: Atmospheric pressure, vented, min. Ø 32 mm

Earth connection: Dry and clean earth pole with low impedance (< 1 Ohm) using an earth cable of > 2.5 mm<sup>2</sup>

Flow rate: 100 - 300 mL/min

Instrument air: Dry and oil free according to ISA-S7.0.01-1996 quality standard for instrument air

Interferences: Metal ions like Aluminium Al(III), Bismuth Bi(II), Cadmium Cd(II), Chromium Cr(III), Cobalt

Co(II), Copper Cu(II), Iron Fe(II), Iron Fe(III), Lead Pb(II), Manganese Mn(II), Magnesium Mg(II), Mercury Hg(II), Palladium Pd(II), Platinum Pt(II), Silver Ag(I), Tin Sn(II), Zinc Zn(II).

Large amounts of colour and turbidity interferes. Fats, oil, proteins, surfactants and tar.

Material: Hinged part: Thermoform ABS, door: PMMA

Wall section: Galvanised steel, powder coated

Measurement method: Colorimetric measurement using DMG colour solution

Measuring range:  $10 - 500 \mu g/L \text{ Ni}$ 

Optional:

 $5 - 125 \mu g/L$ 

 $5 - 250 \mu g/L$ 

80 - 2000 µg/L (with internal dilution)

160 - 4000 μg/L (with internal dilution)

1 - 50 mg/L (with internal dilution)

Model: EZ1027

Number of sample streams: 1, 2, 4, or 8

Parameter: Nickel Ni(II), dissolved
Power: 100 - 240 VAC, 50/60 Hz

Max. power consumption: 120 VA

Power supply: 100 - 240 VAC, 50/60 Hz

Precision: Better than 2% full scale range for standard test solutions

Protection class: Analyser cabinet: IP44 / Panel PC: IP65

Reagent Requirements: Keep between 10 - 30 °C
Sample pressure: By external overflow vessel

Sample quality: Maximum particle size 100  $\mu$ m, < 0.1 g/L; Turbidity < 50 NTU

Sample temperature: 10 - 30 °C

Validation: Automatic; frequency freely programmable

Warranty: 24 months
Weight: 25 kg

What's included?: EZ1027 Nickel Analyser, Instruction Manual, 1 x Double Bit Door Key, 1 x Mounting Brackets

and Empty Containers for Reagents with Fittings

EZ1027 Nickel Analyser, Instruction Manual, 1 x Double Bit Door Key, 1 x Mounting Brackets Fittings	and Empty Containers for Reagents with